



FOCUS FLEX L19

Robust and punchy, the Focus Flex L19 from ADJ Lighting is a versatile moving head luminaire capable of creating wash, beam and pixel effects. Designed to provide lighting designers with both flexibility and creative potential, it is ideal for event production and rental applications as well as for permanent installation in concert halls, theatres, nightclubs and churches.

The fixture is powered by an array of nineteen potent 40-Watt 4-in-1 RGBL color mixing LEDs, each of which can be controlled independently. Through mixing the intensity of the primary LED colors, a huge gamut of output colors can be created to suit any mood or desired look. The fixture features a convenient Virtual CMY mode, which allows control alongside native CMY color mixing fixtures using hardware/software CMY color picker/palette tools. It also offers Virtual Foreground and Background Color Wheel control as well as white light output with variable color temperature of between 2700K to 10,000K. This can be accessed either via linear control or a collection of 10 convenient presets. Meanwhile, through controlling the nineteen LEDs independently, the fixture can be used to generate impressive pixel-mapped effects. All of the LEDs used to construct the Focus Flex L19 are color calibrated to ensure uniform output of fixtures from different batches.

Motorized zoom allows the field angle of the Focus Flex L19 to be altered remotely between a wide 50-degrees and narrow 5-degrees, which allows it to be used for creating both broad washes and concise beams. Its quick motor movement allows for the creation of stunning high-impact aerial effects, while 16-bit fine pan & tilt motor control ensures precise positioning.

A flexible fixture, the Focus Flex L19 offers a range of 5 DMX mode options, appropriate to different applications, as well as a variety of customizable options, including selectable LED refresh rate and dimming modes. These are accessed through a color LCD display panel with 6-button menu interface located on the side panel of the fixture alongside a USB port which can be utilized for easy updates of future firmware releases.

Light Source:

- 19 x 40-Watt RGBL LEDs (50,000 hr.)
- CRI: 83.4
- CT: 2,700K ~ 10,000K
- 39,975 lux / 4.3° beam @ 16' (5m)
- 1,422 lux / 28.3° beam @ 16' (5m)
- Lumens: 7,814 (Zoomed Out, Full On)



Features:

- Moving Light Pixel Wash
- Individual Pixel Control
- Built-In Pixel Effect Programs
- Electronic Strobe / Dimmer
- Pan/Tilt: 540/630 x 260
- Beam Angle: 4.3° ~ 29°
- Field Angle: 5° ~ 50°
- Color Calibrated Pixels so units match from batch to batch
- Virtual CMY DMX Control Modes
- Virtual Foreground and Background Color Wheel Control
- Selectable LED Refresh Rates (900 Hz~25K Hz)
- Selectable Dim Modes: Standard, Stage, TV, Arch., Theatre, Stage 2 and user settable Dim Speed (0.1S~10S)
- 4 Dim Curves: Square, Linear, Inv. Square and S. Curve
- 0-100% smooth dimming
- Fan Cooled
- Antenna for WiFLY EXR Wireless DMX

Colors:

- 19x RGBL LED's (Red, Green, Blue and Lime)
- Virtual CMY DMX Control Modes
- Virtual Foreground and Background Color Wheel Control
- Built-In Color Macros
- 2,700K ~ 10,000K Linear White Color Temperature Control
- Color Temperature Presets: 2,700, 3,000, 3,200, 4,000, 4,500, 5,000, 5,600, 6,500, 8,000 and 10,000K

Control:

- 5 DMX Modes - 16/25/98/25 CMY/28 CMY Channel Modes
- Color LCD display with 6-button function menu
- Control: DMX512, ArtNet, sACN and KlingNet Compatible and WiFLY EXR wireless DMX
- Built-In Effect Pixel Programs with Speed and Fade Control
- RDM (Remote Device Management) compliant
- With Wired Digital Communication Network

Pan/Tilt:

- Pan: 540/630 degrees
- Tilt: 250 degrees
- 16-Bit Fine Pan & Tilt
- Pan & Tilt Locks



Beam or Wash Effects (Motorized Zoom: 5 ~ 50°)



Full Pixel Control



LINEAR COLOR TEMPERATURE CONTROL (TUNABLE WHITE)

Connections:

- DMX Connections: 5-pin XLR In/Out
- RJ45 In/Out
- Power Connections: Indoor Locking Power In/Out

Electrical:

- Multi-voltage operation: 90-240V, 50/60Hz
- Max power consumption: 918W @120V

Dimensions & Weight:

- Dimensions (LxWxH): 15.8"L x 10.20"W x 15.97"H
(400x259x405.5mm)
- Weight: 42lbs (19kg)

What's Included:

- 180mm Omega Brackets (2x)
- 1.83M locking power cable
- Safety Cable

Approvals:

- ETL Pending / CE Certified
- IP20



Specifications subject to change without notice

